



Proceq Ground Penetrating Radars

GP8100

Highly productive portable concrete GPR array, enabling quick object detection and superior data collection



Productivity

Boost scanning efficiency with 25cm effective scan width and 80cm penetration depth, one scan is equivalent to 6 classical line scans



Visualization

Detecting objects of all sizes and marking on concrete surfaces has never been so easy and fast with the superline scan view



Density

The high scan rate of 1'200 scans/s enables a very dense GPR data collection in only one superline scan, which can be visualized in 6 classical line scans



Software / Workspace App

Measurement modes	Superline Scan (1000m / 3281 ft)
	Area Scan (with Flexible Grid up to 100m2 / 1076 ft2)
Review modes	Superline scan ¹
	A-scan (incl. envelope)
	Migrated view
	Non-migrated view
	Split view ¹
	Time-Slice view ² Basic
	3D view
Advanced visualization	AR
	Time-Slice view Pro
	3D view
Reporting	Augmented Reality (AR)
	Workspace integration
	Automatic Logbook
	SEG-Y export
	Instant report generation
Export formats	Share via URL
	JPG
	PNG
	CSV
	SEGY
Display Unit Specs*:	HTML
	Latest Apple® iPad recommended (iPad with iOS 11.0 and higher)
	Screen size: From 7.9" to 12.9"
	Resolution: Up to 2732-by-2048
	Memory: Up to 2TB
Display Unit Sensors*:	Weight: Down to 301 g / 10.6 oz
	Camera: Up to 12MP Wide and 10MP Ultra Wide
	Optional: USB-C, 5G, Face ID
	LiDAR Scanner (optional)
	Three-axis gyro
	Accelerometer
	Ambient light sensor
	Barometer
	Built-in GPS/GNSS

1. GP8100 only; 2. GP8000 & GP8100 only

* Depending on iPad model



Processing Unit / Sensor

Radar technology	Stepped-frequency continuous-wave (SFCW) GPR
Modulated frequency range	400 – 4000 MHz
Penetration depth	80 cm / 31.5 in
Battery	Flight-safe, removable pack, 8x AA (NiMH)
Dimensions	41.5 x 22.5 x 13.2 cm
	16.3 x 8.9 x 5.2 in
Weight	3.0 kg / 6.6 lbs (excl. battery pack)
Ground clearance	0.8 cm / 0.32 in
Antennas	6
Antenna distance to edge	8.3 cm / 3.27 in
Special features	All-wheel drive with high-traction wheels and laser light guidance
	USB-C tethering to power bank
Connections	Wi-Fi (802.11n) to display unit
	USB-C for Wi-Fi restricted areas
Autonomy	3h (Up to 8 hours with off-the-shelf 10'000 mAh power bank, not included)



SWISS  MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

www.screeningeagle.com

[Request a quote](#)



Machine translated & automatically generated (English version prevails); 07.06.2022
Copyright © 2021 Screening Eagle Technologies AG or its affiliates. All rights reserved.